

www.termometal-ada.com



 **TERMOMETAL**

We justify your trust!

Mi opravdavamo poverenje!

ROTACIONE KOSAČICE ROTARY DRUM MOWERS

RotKos 135 RotKos 165

Bočne traktorske kosačice nošene u tri tačke predstavljaju standardnu opremu za košenje pre svega na manjim i srednjim poljoprivrednim gazdinstvima. Svi modeli imaju po dva rotirajuća bubnja gonjena parom zupčanika.

Naše kosačice odlikuje jednostavna ali ojačana konstrukcija i izuzetna trajnost.

Opremljene su sigurnosnim uređajem za otkaćinjanje.

STANDARDNA OPREMA UKLJUČUJE:

- antikorozijska zaštita
- komplet noževa
- kardansko priključno vratilo
- bočna zaštita

Side tractor mowers with three point connection are presenting the standard equipment for mowing that are particularly suitable for smaller and medium size farms. All the models are with two drums driven by a pair of gears.

Our mowers are distinguished with simple but firm construction and high durability.

Equipped with safety device for de-attaching.

STANDARD EQUIPMENT:

- PTO shaft
- protective canvas
- anti-corrosion coating
- set of blades



TEHNIČKE KARAKTERISTIKE Technical details

	RotKos 135	RotKos 165
radna širina / working width	1350 mm	1650 mm
težina / weight	325 kg	400 kg
transportna širina / transport width	1200 mm	1400 mm
transportna dužina / transport length	2500 mm	2850 mm
najveća visina / max. height	1110 mm	1110 mm
broj obrtaja kardanskog vratila / PTO rotation	540 / min	540 / min
broj noževa / blades	6 kom	6 kom
osnovni pogon / main drive	4 klinasta remenika / 4 V belts	3 klinasta remenika / 3 V belts
pogon bubnja / drum drive	konusni zupčanici / conical gears	konusni zupčanici / conical gears
potrebna snaga / required power	18 kW	22 kW
broj mesta za podmazivanje / lubricating spots	5	3
radni učinak / working efficiency	0,8 ha / h	1 ha / h
broj bubnjeva / drums	2	2

ROTACIONA KOSAČICA

ROTARY DRUM MOWER

RotKos 100

Naš novi model kosačice je namenjen za upotrebu na kultivatorima koji imaju mogućnost okretanja upravljača za 180 stepeni. Priključni element za ovu kosačicu prilagođen je različitim tipovima traktora. Pogodna je za rad u voćnjacima, vinogradima kao i za održavanje gradskih zelenih površina. Zbog izuzetno dobrog kopiranja tla od čak 20 stepeni posebno je pogodna za upotrebu na terenima sa većim nagibima zemljišta.

POSEBNE KARAKTERISTIKE:

- siguran i bezbedan rad
- lako priključivanje
- jednostavna i brza zamena noževa
- jednostavan transport

STANDARDNA OPREMA:

- priključni element
- bočna zaštita
- antikorozijska zaštita
- set noževa

Prilikom poručivanja ovog tipa kosačice molimo da navedete tip kultivatora i smer okretanja kardana.



Our newest model of double drum rotary mower is adaptable to motocultivators whose handle bar can be turned for 180 degrees. The attaching element varies depending on the type of motor-cultivator. It is particularly suitable for mowing in vineyards, parks and other smaller grass fields.

SPECIAL CHARACTERISTICS:

- safe and smooth performance
- easy attaching
- simple and fast change of blades
- easy transport

STANDARD EQUIPMENT:

- motor-cultivator attachment
- protective canvas
- anticorrosion protection
- set of blades

When ordering this type of mower please indicate the motor-cultivator type and the direction of PTO rotation.

TEHNIČKE KARAKTERISTIKE

Technical details

RotKos 100

radna širina / working width	1000 mm
težina / weight	90 kg
transportna širina / transport width	1120 mm
transportna dužina / transport length	600 mm
najveća visina / max. height	360 mm
broj obrtaja kardanskog vratila / PTO rotation	790 / min
broj noževa / blades	6 kom
pogon bubnja / drum drive	konusni zupčanci / conical gears
potrebna snaga / required power	8-14kW
broj mesta za podmazivanje / lubricating spots	1
radni učinak / working efficiency	0,5 ha / h
broj bubnjeva / drums	2

ROTACIONI SAKUPLJAČ – PREVRTAČ SENA ROTARY GATHERER - HAY RAKE SUNCE



Namenjen je za sakupljanje, rastresanje i prevrtanje zelene ili suve otkošene travnate mase, usitnjene kukuruzovine i ostalih biljnih ostataka.

SUNCE predstavlja oruđe nošenog tipa, priključuje se na traktore sa vešanjem oruđa I i II kategorije, koji imaju odgovarajući sistem povezivanja u tri tačke.

Sakupljač **SUNCE** odlikuje jednostavna i ojačana konstrukcija, višestruka namena i minimalna potrošnja energije.

Zbog izuzetno dobrog kopiranja tla pogodan je za upotrebu na svim terenima.



***SUNCE HAY RAKE** is designed for mowed grass gathering, both green and dry, and for collecting dried hashed up corn stalks. This work proceeds to baling with presses, rolling balers or hay loaders. This implement can also be used for hay loosening, to expose the green hay to the sun in order to speed up the drying process.*

This is a tractor attaching implement that can be used with tractors of 1st and 2nd category with 3 point hitch.

***SUNCE HAY RAKE** provides maximum performance with minimum maintenance.*



TEHNIČKE KARAKTERISTIKE Technical details



radni zahvat / working width	2,4 m
težina / weight	200 kg
transportna širina / transport width	2,4 m
transportna brzina / transport speed	do 20 km / h
broj sabirnih točkova / collecting wheels	4
broj sabirnih elemenata u točku / collecting elements per wheel	20
potrebna snaga / required power	min 14 kW
broj mesta za podmazivanje / lubricating spots	7
radni učinak / working efficiency	3 ha / h



RASIPAČ MINERALNOG ĐUBRIVA FERTILIZER SPREADER

FERTI

Rasipač FERTI upotrebljava se za rasipanje suvih, granuliranih, praškastih, kristalnih veštačkih đubriva i kreča. Disk sa 6 lopatica omogućuje puno ravnomjerniju distribuciju veštačkih đubriva po površini. Dupla regulacija distribuirane količine omogućava rasipanje samo po desnoj, samo po levoj strani ili po ukupnoj površini.

Rasipač FERTI dostupan je u tri modela:

FERTI 300, FERTI 400 i FERTI 500

PREDNOSTI:

- metalni rezervoar
- snažna noseća konstrukcija
- disk sa šest lopatica
- dupla regulacija izlazne količine
- mogućnost fiksiranja regulacije
- kačenje za I ili II kategoriju
- mogućnost kačenja prikolice
- poboljšanje stabilnosti rasipača
- levak pričvršćen sa pet zavrtnja
- zaštita od rasipanja po traktoru



Fertilizer spreader FERTI is used for spreading of dry mineral granulated, powdery and crystallized fertilizer and for lime. Double regulation allows separate left/right control. Much more uniform spreading is achieved by 6 spreading vanes on spreading disc.

FERTI is available in three models:

FERTI 300, FERTI 400 i FERTI 500

ADVANTAGES:

- metal hopper
- rigid holding frame
- spreading disc with 6 vanes
- double regulation for spreading
- 3-point linkage I and II cat.
- linkage for trailer
- additional supports for stability
- hopper fixed with 5 bolts
- spreading guard

TEHNIČKE KARAKTERISTIKE Technical details

	FERTI 300	FERTI 400	FERTI 500
Zapremina (l)	260	320	380
Maximalna nosivost (kg)	350	450	550
Širina rasipanja (m)	6 - 18	6 - 18	6 - 18
Broj obrtaja kardana	540	540	540
Težina (kg)	54	58	59

O TERMOMETALU

1986. god. pod nazivom **TERMOMETAL** osnovana je zanatska radionica za termičku obradu metala koja je 1992. prerasla u preduzeće za izradu opreme i termičku obradu metala u privatnoj svojini.

Sa proizvodnjom rezervnih delova za poljoprivredu započeli smo 1996. godine a nekoliko godina zatim započeli smo i proizvodnju priključne poljoprivredne mehanizacije. Stalnim ulaganjem u svoje proizvodne procese, modernizacijom svojih tehnoloških mogućnosti kao i stručnim usavršavanjem svojih zaposlenih izgradili smo stabilnu i kvalitetnu proizvodnju proizvoda za potrebe poljoprivrede. Naša ponuda obuhvata preko 1200 različitih rezervnih delova za poljoprivrednu mehanizaciju kao i priključne mašine: rotacione kosačice, rotacioni sakupljač sena i rasipače mineralnog đubriva.



Poseban segment naše proizvodnje predstavlja izrada rezervnih delova za poljoprivredne mašine po zahtevu kupca na osnovu dostavljenog uzorka. Naši visoko stručni i iskusni tehničari i inženjeri uvek su spremni da odgovore i najsloženijim zahtevima naših kupaca. Tokom svih ovih godina koliko postojimo osnovni cilj bio nam je da isporučimo kvalitetan proizvod krajnjem korisniku. Potvrda našeg uspeha u tome, pored brojnih nagrada osvojenih za kvalitet proizvoda, jesu naši zadovoljni kupci čije poverenje uvek nastojimo da opravdamo. Pažljivim odabirom materijala koje koristimo u proizvodnji obezbeđujemo ne samo visok kvalitet naših proizvoda već i uspostavljanje pravog odnosa između tehnologije i materijala koji koristimo, kako bismo zadovoljili i najviše standarde kvaliteta i dostigli najpovoljnije cene.

TERMOMETAL DOO danas je moderno, fleksibilno preduzeće spremno da odgovori tržišnim trendovima i rastućoj tražnji za našim proizvodima.

***TERMOMETAL** was founded in 1986. as a small work shop for heat treatment.*

In 1992. it has grown into private limited liability company and in 1996 we have started the production of parts for agricultural machines.

With constant investments in our production processes, modernization of our equipment and technological capacities we have built a stable and quality production of agricultural implements: rotary mowers, hay rake and fertilizer spreaders and different spare parts for agricultural machines.



Special segment of our production is the production of parts and components according to customers drawings or samples.

From the very beginning the main goal of our business was to provide quality products to our customers. The confirmation of our success, beside many awards received for the quality of our products are our regular customers whose trust we constantly strive to justify. Our highly skilled and experienced engineers and technicians are always ready to respond even to the most demanding and complex customers requests.

*Today, **TERMOMETAL** is a modern and flexible company ready to respond to the market trends and to the increasing demand of it's products.*